

		<h1>Technical Sheet</h1> <h2>Round Bucket 2.1 L- ø170 mm - SuperLift</h2>	
Volume			
Volume under Lid	2100 ml +/- 40 ml	Sealable Volume	2300ml +/- 40 ml
Dimensions			
Shape	Conical Round	Height without Lid	132 mm ± 1 mm
Top outside diameter without lid	170 mm ± 1 mm	Height with Lid	133 mm ± 1 mm
Top outside diameter with lid	170 mm ± 1 mm		
Bottom outside diameter	141 mm ± 1 mm		
Weight			
Body	65 g ± 2 g		
Lid	17.5 g ± 1g		
Handle	3 g ± 0.5g		
Closure System			
Standard	Closing by Lid	Closure Type	SuperLift
Protective Collar	Yes	Tamper Evidence	Yes
Handle			
Standard	Plastic	Option	NA
Decoration			
Body	IML/NEUTRAL	Lid	NEUTRAL
Raw Material			
Raw Material used	Polypropylene (granules)		
Dye	White as Standard, others on demand		
Alimentary	Materials and dyes suitable for contact with foodstuffs	 	
Thermal Properties			
Hot Temperatures	<p>The material use is characterized by very good heat resistance. Our packaging is therefore suitable for hot filling. Once subjected to high temperatures, they become more flexible, and their immediate storage must be done with the necessary care. After cooling, they regain their usual strength.</p> <p>The customer who uses Galion packaging at high temperatures is deemed to have already tested and validated this packaging in advance with the intended application.</p>		
Cold Temperatures	<p>The standard resins used are suitable for freezing our packaging at negative temperatures. Very low temperatures require the use of special resin available on request.</p> <p>The customer who uses Galion packaging at low temperatures is deemed to have already tested and validated this packaging in advance with the intended application.</p>		
Packaging and Delivery			
	Body		Lid
Conditioning	Unit	Plastic bag	Plastic bag
	Dimensions (HxWxL)	-	-
	Capacity (in pieces)	60	60
Delivery	Unit	BULK/PALLETS	BULK/PALLETS
	Dimensions (HxWxL)	-	-
	Capacity (in pieces)	60	60
General Specifications			
Stacking	It is the customer's responsibility to carry out internal stacking tests in advance to ensure that transport conditions are suitable for him.		
Uses	The packaging described in this technical data sheet is manufactured in accordance with the requirements of the national regulations applicable to plastic materials and articles intended to come into contact with foodstuffs. The customer cannot deny that he or she was aware of the data mentioned in this technical data sheet and that he or she had checked the content suitability before using the packaging.		
Lifetime	Compliance of the packaging with the specifications given in this technical data sheet is guaranteed for 12 months from the date of delivery; and this subject to preserving the packaging during the stackage and storage.		
Quality Standards	Degradation of the technical characteristics not exceeding 0,1% (1item out of 1000) during the warranty period cannot in any case be interpreted as a defect.		

