

Reference Document : FE.P.06 Creation Date : 03/12/2020



Technical Sheet

Bucket 2.5 L- Rectangular - SuperCube

	e		Bucket 2.5 L- Rectangular - SuperCube		
Volume					
Volume under Lid	2500 ml +/- 50 ml		Sealable Volume	2600 ml +/- 50 ml	
Dimensions					
Shape	Rectangular		Length	201mm ± 1 mm	
Height	132mm ± 1 mm		Width	139 mm ± 1 mm	
Weight					
Body	68 g ± 2 g				
Lid	18.5g ± 1g				
Handle	4.5 g ± 0.5g				
Closure System			:		
Standard	Closing by Lid		Closure Type	SuperCube	
Protective Collar	Yes		Tamper Evidence	Yes	
Handle					
Standard	Plastic		Option	NA	
Decoration					
Body	IML/NEUTRAL		Lid	IML/NEUTRAL	
Raw Material					
Raw Material used	Polypropylene (granu	ıles)			
Dye	White as Standard, o	thers on deman	d		
Alimentary	Materials and dyes s	uitable for conta	ct with foodstuffs	<u></u> 57"	
Thermal Properties					
Hot Temperatures				ur packaging is therefore suitable for hot fill and their immediate storage must be done v	
Cold Temperatures	The standard resins require the use of spe	ses Galion pack e with the intend used are suitable ecial resin availa	aging at high temperatures is ded application. e for freezing our packaging at the on request.	deemed to have already tested and validate t negative temperatures. Very low temperat	
Cold Temperatures	The customer who us packaging in advance The standard resins require the use of spe	ses Galion packa e with the intend used are suitable ecial resin availa ses Galion packa	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is described.		
Cold Temperatures Packaging and De	The customer who us packaging in advance The standard resins require the use of specific the customer who us packaging in advance	ses Galion packa e with the intend used are suitable ecial resin availa ses Galion packa	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is described.	t negative temperatures. Very low temperat	
·	The customer who us packaging in advance The standard resins require the use of specific the customer who us packaging in advance	ses Galion pack; e with the intend used are suitable ecial resin availa ses Galion pack; e with the intend	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is described.	t negative temperatures. Very low temperat	
Cold Temperatures Packaging and De	The customer who us packaging in advance The standard resins require the use of specific the customer who us packaging in advance	ses Galion pack; e with the intend used are suitable ecial resin availa ses Galion pack; e with the intend	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application.	t negative temperatures. Very low temperat eemed to have already tested and validated	
Packaging and De	The customer who us packaging in advance The standard resins require the use of spe The customer who us packaging in advance	ses Galion packa e with the intend used are suitabl ecial resin availa ses Galion packa e with the intend	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application.	t negative temperatures. Very low temperat eemed to have already tested and validated Lid	
Packaging and De	The customer who us packaging in advance The standard resins require the use of spe The customer who us packaging in advance Slivery Unit	ses Galion packa e with the intend used are suitabl ecial resin availa ses Galion packa e with the intend	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application.	t negative temperatures. Very low temperate eemed to have already tested and validated Lid Cardboards	
Packaging and De	The customer who us packaging in advance The standard resins require the use of specific the use of specific the customer who us packaging in advance Unit Dimensions (HxWxL)	ses Galion packa e with the intend used are suitablecial resin availa ses Galion packa e with the intend	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	t negative temperatures. Very low temperat eemed to have already tested and validated Lid Cardboards 380X395X605	
Packaging and De	The customer who us packaging in advance The standard resins require the use of spe The customer who us packaging in advance Livery Unit Dimensions (HxWxL) Capacity (in pieces)	ses Galion pack: e with the intend used are suitablecial resin availe ses Galion pack: e with the intend Bo Plastic bag	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	t negative temperatures. Very low temperat eemed to have already tested and validated Lid Cardboards 380X395X605	
Packaging and De	The customer who us packaging in advance The standard resins a require the use of specific the customer who us packaging in advance Livery Unit Dimensions (HxWxL) Capacity (in pieces) Unit Dimensions (HxWxL) Capacity (in pieces)	ses Galion pack: e with the intend used are suitablecial resin availe ses Galion pack: e with the intend Bo Plastic bag	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	Lid Cardboards 380X395X605 900 Cardboard	
Packaging and De	The customer who us packaging in advance The standard resins or require the use of specific the use of sp	ses Galion packa e with the intend used are suitable ecial resin availa ses Galion packa e with the intend Bo Plastic bag 60 BULK/PALLETT 60	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	Lid Cardboards 380X395X605 900 Cardboard 380X395X605 900	
Packaging and De Conditioning Delivery General Specificat	The customer who us packaging in advance The standard resins or require the use of specific the use of sp	ses Galion packa e with the intend used are suitable ecial resin availa ses Galion packa e with the intend Bo Plastic bag 60 BULK/PALLETT 60	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	Lid Cardboards 380X395X605 200 Cardboard 380X395X605	
Packaging and De Conditioning Delivery General Specificat Stacking	The customer who us packaging in advance The standard resins or require the use of specific the use of specific the customer who us packaging in advance Unit Dimensions (HxWxL) Capacity (in pieces) Unit Dimensions (HxWxL) Capacity (in pieces) It is the customer's resultable for him. The packaging descriptional regulations at The customer cannot	ses Galion packate with the intended used are suitable ecial resin availates ses Galion packate with the intended by the inten	aging at high temperatures is ded application. e for freezing our packaging at lible on request. aging at low temperatures is ded application. dy	Lid Cardboards 380X395X605 900 Cardboard 380X395X605 900 in advance to ensure that transport conditioned in this technical data sheet and that the control of the contro	
·	The customer who us packaging in advance The standard resins or require the use of specific packaging in advance. The customer who us packaging in advance. It is the customer's resuitable for him. The packaging descriptions a The customer cannot she had checked the packaging in advance.	ses Galion pack: e with the intend used are suitablecial resin available exist available exist resin available exist resint resi	aging at high temperatures is ded application. e for freezing our packaging at ble on request. aging at low temperatures is ded application. ddy	Lid Cardboards 380X395X605 900 Cardboard 380X395X605 900 in advance to ensure that transport conditioned in this technical data sheet and that the control of the contro	